

HTML <ILAYER> TAG

http://www.tutorialspoint.com/html/html_ilayer_tag.htm

Copyright © tutorialspoint.com

Description

The HTML <ilayer> tag is used to create a layer that occupies space in the containing text flow. Subsequent content is placed after the space occupied by the <ilayer>.

This is in contrast to the <layer> tag, which creates a layer above the containing text flow, allowing subsequent content to be placed under the layer just created.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML ilayer Tag</title>
</head>
<body>
This <ilayer top="4">word</ilayer> is shifted down, while
this <ilayer left="10">one</ilayer> is shifted over. With a negative
value, words can be moved <ilayer top="-4">up</ilayer> and to
the <ilayer left="-10">left</ilayer>.
</body>
</html>
```

This will produce following result:

This word is shifted down, while this one is shifted over. With a negative value, words can be moved up and to the left.

The result will only work on Netscape 4.

Global Attributes

This tag supports all the global attributes described in - [HTML Attribute Reference](#)

Specific Attributes

The HTML <ilayer> tag also supports following additional attributes:

Attribute	Value	Description
above	layer name	The name of the inline layer that will be positioned directly above the current layer in the z-order.
background	URL	A filename or URL for an image upon which the inline layer's text and images will appear.
below	layer name	The name of the inline layer that will be positioned directly below the current layer in the z-order.
bgcolor	rgbx, x, x #xxxxxx colorname	The color to use for the inline layer background.
clip	number	The coordinates of the inline layer's viewable area.
height	pixels	The inline layer's height, in pixels.
left	number	The position of the left side of the inline layer. If the current inline layer is part of another layer.called the

		parent layer-then the position is relative to the parent layer.
name	layer name	The name of the inline layer.
pagex	number	The position of the left side of the inline layer relative to the browser window.
pagey	number	The position of the top of the inline layer relative to the browser window.
src	URL	The URL of a page that will appear inside the inline layer.
top	number	The position of the top of the inline layer. If the current inline layer is part of another layer--called the parent layer--then the position is relative to the parent layer.
visibility	show hide inherit	Determines whether the inline layer is visible.
width	pixels	The inline layer's width, in pixels.
z-index	number	The inline layer's position within the z-order. Inline layers with higher Z-INDEX values are positioned above inline layers with lower Z-INDEX values.

Event Attributes

This tag supports all the event attributes described in - [HTML Events Reference](#)

Browser Support

Chrome	Firefox	IE	Opera	Safari	Android
No	No	No	No	No	No

Loading [Mathjax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js