

APACHE POI WORD - QUICK GUIDE

http://www.tutorialspoint.com/apache_poi_word/apache_poi_word_quick_guide.htm Copyright © tutorialspoint.com

APACHE POI WORD - OVERVIEW

Many a time, a software application is required to generate reference documents in Microsoft Word file format. Sometimes, an application is even expected to receive Word files as input data.

Any Java programmer who wants to produce MS-Office files as output must use a predefined and read-only API to do so.

What is Apache POI?

Apache POI is a popular API that allows programmers to create, modify, and display MS-Office files using Java programs. It is an open source library developed and distributed by Apache Software Foundation to design or modify MS-Office files using Java program. It contains classes and methods to decode the user input data or a file into MS-Office documents.

Components of Apache POI

Apache POI contains classes and methods to work on all OLE2 Compound documents of MS-Office. The list of components of this API is given below:

- **POIFS** *PoorObfuscationImplementationFileSystem* : This component is the basic factor of all other POI elements. It is used to read different files explicitly.
- **HSSF** *HorribleSpreadSheetFormat* : It is used to read and write .xls format of MS-Excel files.
- **XSSF** *XMLSpreadSheetFormat* : It is used for .xlsx file format of MS-Excel.
- **HPSF** *HorriblePropertySetFormat* : It is used to extract property sets of the MS-Office files.
- **HWPF** *HorribleWordProcessorFormat* : It is used to read and write .doc extension files of MS-Word.
- **XWPF** *XMLWordProcessorFormat* : It is used to read and write **.docx** extension files of MS-Word.
- **HSLF** *HorribleSlideLayoutFormat* : It is used to read, create, and edit PowerPoint presentations.
- **HDGF** *HorribleDiaGramFormat* : It contains classes and methods for MS-Visio binary files.
- **HPBF** *HorriblePuBlisherFormat* : It is used to read and write MS-Publisher files.

This tutorial guides you through the process of working on MS-Word files using Java. Therefore the discussion is confined to HWPF and XWPF components.

APACHE POI WORD - INSTALLATION

This chapter takes you through the process of setting up Apache POI on Windows and Linux based systems. Apache POI can be easily installed and integrated with your current Java environment, following a few simple steps without any complex setup procedures. User administration is required while installation.

System Requirements

JDK	Java SE 2 JDK 1.5 or above
Memory	1 GB RAM <i>recommended</i>
Disk Space	No minimum requirement
Operating System Version	Windows XP or above, Linux

Let us now proceed with the steps to install Apache POI.

Step 1: Verify your Java Installation

First of all, you need to have Java Software Development Kit *SDK* installed on your system. To verify this, execute any of the two commands mentioned below, depending on the platform you are working on.

If the Java installation has been done properly, then it will display the current version and specification of your Java installation. A sample output is given in the following table:

Platform	Command	Sample Output
Windows	Open command console and type: \>java -version	Java version "1.7.0_60" Java <i>TM</i> SE Run Time Environment <i>build</i> 1.7.0 ₆₀ - b19 Java Hotspot <i>TM</i> 64-bit Server VM <i>build</i> 24.60 - b09, <i>mixedmode</i>
Linux	Open command terminal and type: \$java -version	java version "1.7.0_25" Open JDK Runtime Environment <i>rhel</i> - 2.3.10.4. <i>el6</i> ₄ - <i>x86</i> ₆₄ Open JDK 64-Bit Server VM <i>build</i> 23.7 - b01, <i>mixedmode</i>

- We assume that the readers of this tutorial have Java SDK version 1.7.0_60 installed on their system.
- In case you do not have Java SDK, download its current version from <http://www.oracle.com/technetwork/java/javase/downloads/index.html> and have it installed.

Step 2: Set your Java Environment

Set the environment variable `JAVA_HOME` to point to the base directory location where Java is installed on your machine. For example,

Platform	Description
Windows	Set <code>JAVA_HOME</code> to <code>C:\ProgramFiles\java\jdk1.7.0_60</code>
Linux	Export <code>JAVA_HOME=/usr/local/java-current</code>

Append the full path of Java compiler location to the System Path.


Platform	Description
Windows	Append the String " <code>C:\Program Files\Java\jdk1.7.0_60\bin</code> " to the end of the system variable <code>PATH</code> .
Linux	Export <code>PATH=PATH:JAVA_HOME/bin/</code>

Execute the command **java - version** from the command prompt as explained above.

Step 3: Install Apache POI Library

Download the latest version of Apache POI from <http://poi.apache.org/download.html> and unzip its contents to a folder from where the required libraries can be linked to your Java program. Let us assume the files are collected in a folder on C drive.

The following images shows the directories and the file structure inside the downloaded folder:



Add the complete path of the five **jar**s as highlighted in the above image to the CLASSPATH.

Platform Description

Windows

Append the following strings to the end of the user variable CLASSPATH:

"C:\poi-3.9\poi-3.9-20121203.jar;"

"C:\poi-3.9\poi-ooxml-3.9-20121203.jar;"

"C:\poi-3.9\poi-ooxml-schemas-3.9-20121203.jar;"

"C:\poi-3.9\ooxml-lib\dom4j-1.6.1.jar;"

"C:\poi-3.9\ooxml-lib\xmlbeans-2.3.0.jar;.;"

Linux

Export CLASSPATH=\$CLASSPATH:

/usr/share/poi-3.9/poi-3.9-20121203.tar:

/usr/share/poi-3.9/poi-ooxml-schemas-3.9-20121203.tar:

/usr/share/poi-3.9/poi-ooxml-3.9-20121203.tar:

/usr/share/poi-3.9/ooxml-lib/dom4j-1.6.1.tar:

/usr/share/poi-3.9/ooxml-lib/xmlbeans-2.3.0.tar

APACHE POI WORD - CORE CLASSES

This chapter takes you through the classes and methods of Apache POI for managing a Word document.

Document

This is a marker interface *interfacedonotcontainanymethods*, that notifies that the implemented class can be able to create a word document.

XWPFDocument

This is a class under **org.apache.poi.xwpf.usermodel** package. It is used to create MS-Word Document with .docx file format.

Class Methods:

S. No.	Method and Description
1	commit Commits and saves the document.
2	createParagraph Appends a new paragraph to this document.
3	createTable Creates an empty table with one row and one column as default.
4	createTOC Creates a table of content for Word document.
5	getParagraphs Returns the paragraphs that holds the text of the header or footer.
6	getStyle Returns the styles object used.

For the remaining methods of this class, refer the complete API document at:

<https://poi.apache.org/apidocs/index.html?org/apache/poi/openxml4j/opc/internal/package-summary.html>.

XWPFParagraph

This is a class under **org.apache.poi.xwpf.usermodel** package and is used to create paragraph in a word document. This instance is also used to add all types of elements into word document.

Class Methods:

S. No.	Method and Description
1	createRun Appends a new run to this paragraph.
2	getAlignment Returns the paragraph alignment which shall be applied to the text in this paragraph.
3	setAlignment <i>ParagraphAlignmentalign</i> Specifies the paragraph alignment which shall be applied to the text in this paragraph.
4	setBorderBottom <i>Bordersborder</i> Specifies the border which shall be displayed below a set of paragraphs, which have the same set of paragraph border settings.
5	setBorderLeft <i>Bordersborder</i> Specifies the border which shall be displayed on the left side of the page around the specified paragraph.
6	setBorderRight <i>Bordersborder</i> Specifies the border which shall be displayed on the right side of the page around the specified paragraph.
7	setBorderTop <i>Bordersborder</i> Specifies the border which shall be displayed above a set of paragraphs which have the same set of paragraph border settings.

For the remaining methods of this class, refer the complete API document at:

<https://poi.apache.org/apidocs/index.html?org/apache/poi/openxml4j/opc/internal/package-summary.html>.

XWPFRun

This is a class under **org.apache.poi.xwpf.usermodel** package and is used to add a region of text to the paragraph.

Class Methods:

S. No.	Method and Description
--------	------------------------

- 1 **addBreak**
Specifies that a break shall be placed at the current location in the run content.
- 2 **addTab**
Specifies that a tab shall be placed at the current location in the run content.
- 3 **setColor***java. lang. StringrgbStr*
Sets text color.
- 4 **setFontSize***intsize*
Specifies the font size which shall be applied to all noncomplex script characters in the content of this run when displayed.
- 5 **setText***java. lang. Stringvalue*
Sets the text of this text run.
- 6 **setBold***booleanvalue*
Specifies whether the bold property shall be applied to all non-complex script characters in the content of this run when displayed in a document.

For the remaining methods of this class, refer the complete API document at:

<https://poi.apache.org/apidocs/index.html?org/apache/poi/openxml4j/opc/internal/package-summary.html>.

XWPFStyle

This is a class under **org.apache.poi.xwpf.usermodel** package and is used to add different styles to the object elements in a word document.

Class Methods:

S. No.	Method and Description
1	getNextStyleID It is used to get StyleID of the next style.
2	getStyleId It is used to get StyleID of the style.
3	getStyles

It is used to get styles.

4

setStyleId*java.lang.String styleId*

It is used to set styleID.

For the remaining methods of this class, refer the complete API document at:

<https://poi.apache.org/apidocs/index.html?org/apache/poi/openxml4j/opc/internal/package-summary.html>.

XWPFTable

This is a class under **org.apache.poi.xwpf.usermodel** package and is used to add table data into a word document.

Class Methods:

S. No.	Method and Description
1	addNewCol Adds a new column for each row in this table.
2	addRow <i>XWPFTableRow row, int pos</i> Adds a new Row to the table at position pos.
3	createRow Creates a new XWPFTableRow object with as many cells as the number of columns defined in that moment.
4	setWidth <i>int width</i> Sets the width of the column.

For the remaining methods of this class, refer the complete API document at:

<https://poi.apache.org/apidocs/index.html?org/apache/poi/openxml4j/opc/internal/package-summary.html>.

XWPFFWordExtractor

This is a class under **org.apache.poi.xwpf.extractor** package. It is a basic parser class used to extract the simple text from a Word document.

Class Methods:

S. No.	Method and Description
1	

getText

Retrieves all the text from the document.

For the remaining methods of this class, refer the complete API document at: <https://poi.apache.org/apidocs/index.html?org/apache/poi/openxml4j/opc/internal/package-summary.html>.

APACHE POI WORD - DOCUMENT

Here the term 'document' refers to a MS-Word file. After completion of this chapter, you will be able to create new documents and open existing documents using your Java program.

Create Blank Document

The following simple program is used to create a blank MS-Word document:

```
import java.io.File;
import java.io.FileOutputStream;
import org.apache.poi.xwpf.usermodel.XWPFDocument;

public class CreateDocument
{
    public static void main(String[] args) throws Exception
    {
        //Blank Document
        XWPFDocument document= new XWPFDocument();
        //Write the Document in file system
        FileOutputStream out = new FileOutputStream(
            new File("createdocument.docx"));
        document.write(out);
        out.close();
        System.out.println(
            "createdocument.docx written successfully");
    }
}
```

Save the above Java code as **CreateDocument.java**, and then compile and execute it from the command prompt as follows:

```
$javac CreateDocument.java
$java CreateDocument
```

If your system environment is configured with the POI library, it will compile and execute to generate a blank Excel file named **createdocument.docx** in your current directory and display the following output in the command prompt:

```
createdocument.docx written successfully
```

APACHE POI WORD - PARAGRAPH

In this chapter you will learn how to create a Paragraph and how to add it to a document using Java. Paragraph is a part of a page in a Word file.

After completing this chapter, you will be able to create a Paragraph and perform read operations on it.

Create a Paragraph

First of all, let us create a Paragraph using the referenced classes discussed in the earlier chapters. By following the previous chapter, create a Document first, and then we can create a Paragraph.

The following code snippet is used to create a spreadsheet:

```
//Create Blank document
XWPFDocument document= new XWPFDocument();
//Create a blank spreadsheet
XWPFParagraph paragraph = document.createParagraph();
```

Run on Paragraph

You can enter the text or any object element, using **Run**. Using Paragraph instance you can create **run**.

The following code snippet is used to create a Run.

```
XWPFRun run=paragraph.createRun();
```

Write into a Paragraph

Let us try entering some text into a document. Consider the below text data:

```
At tutorialspoint.com, we strive hard to provide quality tutorials for self-learning
purpose in the domains of Academics, Information Technology, Management and Computer
Programming Languages.
```

The following code is used to write the above data into a paragraph.

```
import java.io.File;
import java.io.FileOutputStream;
import org.apache.poi.xwpf.usermodel.XWPFDocument;
import org.apache.poi.xwpf.usermodel.XWPFParagraph;
import org.apache.poi.xwpf.usermodel.XWPFRun;

public class CreateParagraph
{
    public static void main(String[] args)throws Exception
    {
        //Blank Document
        XWPFDocument document= new XWPFDocument();
        //Write the Document in file system
        FileOutputStream out = new FileOutputStream(
            new File("createparagraph.docx"));

        //create Paragraph
        XWPFParagraph paragraph = document.createParagraph();
        XWPFRun run=paragraph.createRun();
        run.setText("At tutorialspoint.com, we strive hard to " +
            "provide quality tutorials for self-learning " +
            "purpose in the domains of Academics, Information " +
            "Technology, Management and Computer Programming
            Languages.");
        document.write(out);
        out.close();
        System.out.println("createparagraph.docx written successfully");
    }
}
```


Save the above Java code as **CreateParagraph.java**, and then compile and run it from the command prompt as follows:

```
$javac CreateParagraph.java
$java CreateParagraph
```

It will compile and execute to generate a Word file named **createparagraph.docx** in your current directory and you will get the following output in the command prompt:

createparagraph.docx written successfully

The **createparagraph.docx** file looks as follows.



APACHE POI WORD - BORDERS

In this chapter, you will learn how to apply border to a paragraph using Java programming.

Applying Border

The following code is used to apply Borders in a Document:

```
import java.io.File;
import java.io.FileOutputStream;
import org.apache.poi.xwpf.usermodel.Borders;
import org.apache.poi.xwpf.usermodel.XWPFDocument;
import org.apache.poi.xwpf.usermodel.XWPFParagraph;
import org.apache.poi.xwpf.usermodel.XWPFRun;

public class ApplyingBorder
{
    public static void main(String[] args) throws Exception
    {
        //Blank Document
        XWPFDocument document= new XWPFDocument();

        //Write the Document in file system
        FileOutputStream out = new FileOutputStream(
            new File("applyingborder.docx"));

        //create paragraph
        XWPFParagraph paragraph = document.createParagraph();

        //Set bottom border to paragraph
        paragraph.setBorderBottom(Borders.BASIC_BLACK_DASHES);

        //Set left border to paragraph
        paragraph.setBorderLeft(Borders.BASIC_BLACK_DASHES);

        //Set right border to paragraph
        paragraph.setBorderRight(Borders.BASIC_BLACK_DASHES);

        //Set top border to paragraph
        paragraph.setBorderTop(Borders.BASIC_BLACK_DASHES);

        XWPFRun run=paragraph.createRun();
```

```

run.setText("At tutorialspoint.com, we strive hard to " +
"provide quality tutorials for self-learning " +
"purpose in the domains of Academics, Information " +
"Technology, Management and Computer Programming " +
"Languages.");

document.write(out);
out.close();
System.out.println("applyingborder.docx written successfully");
}
}

```

Save the above code in a file named **ApplyingBorder.java**, compile and execute it from the command prompt as follows:

```

$javac ApplyingBorder.java
$java ApplyingBorder

```


If your system is configured with the POI library, then it will compile and execute to generate a Word document named **applyingborder.docx** in your current directory and display the following output:

```

applyingborder.docx written successfully

```

The **applyingborder.docx** file looks as follows:



APACHE POI WORD - TABLES

In this chapter, you will learn how to create a table of data in a document. You can create a table data by using **XWPFTable** class. By adding each **Row** to table and adding each **cell** to **Row**, you will get table data.

Create Table

The following code is used to creating table in a document:

```

import java.io.File;
import java.io.FileOutputStream;
import org.apache.poi.xwpf.usermodel.XWPFDocument;
import org.apache.poi.xwpf.usermodel.XWPFTable;
import org.apache.poi.xwpf.usermodel.XWPFTableRow;

public class CreateTable
{

```

```

public static void main(String[] args) throws Exception
{
//Blank Document
XWPFDocument document= new XWPFDocument();

//Write the Document in file system
FileOutputStream out = new FileOutputStream(
new File("create_table.docx"));

//create table
XWPFTable table = document.createTable();
//create first row
XWPFTableRow tableRowOne = table.getRow(0);
tableRowOne.getCell(0).setText("col one, row one");
tableRowOne.addNewTableCell().setText("col two, row one");
tableRowOne.addNewTableCell().setText("col three, row one");
//create second row
XWPFTableRow tableRowTwo = table.createRow();
tableRowTwo.getCell(0).setText("col one, row two");
tableRowTwo.getCell(1).setText("col two, row two");
tableRowTwo.getCell(2).setText("col three, row two");
//create third row
XWPFTableRow tableRowThree = table.createRow();
tableRowThree.getCell(0).setText("col one, row three");
tableRowThree.getCell(1).setText("col two, row three");
tableRowThree.getCell(2).setText("col three, row three");

document.write(out);
out.close();
System.out.println("create_table.docx written successully");
}
}

```

Save the above code in a file named **CreateTable.java**. Compile and execute it from the command prompt as follows:

```

$javac CreateTable.java
$java CreateTable

```


It generates a Word file named **createtable.docx** in your current directory and display the following output on the command prompt:

```

createtable.docx written successfully

```

The **createtable.docx** file looks as follows:



FONT STYLE AND ALIGNMENT

This chapter shows how to apply different font styles and alignments in a Word document using Java. Generally, Font Style contains: Font size, Type, Bold, Italic, and Underline. And Alignment is categorized into left, center, right, and justify.

Font Style

The following code is used to set different styles of font:

```
import java.io.File;
import java.io.FileOutputStream;
import org.apache.poi.xwpf.usermodel.VerticalAlign;
import org.apache.poi.xwpf.usermodel.XWPFDocument;
import org.apache.poi.xwpf.usermodel.XWPFParagraph;
import org.apache.poi.xwpf.usermodel.XWPFRun;

public class FontStyle
{
    public static void main(String[] args) throws Exception
    {
        //Blank Document
        XWPFDocument document= new XWPFDocument();

        //Write the Document in file system
        FileOutputStream out = new FileOutputStream(
            new File("fontstyle.docx"));

        //create paragraph
        XWPFParagraph paragraph = document.createParagraph();

        //Set Bold an Italic
        XWPFRun paragraphOneRunOne = paragraph.createRun();
        paragraphOneRunOne.setBold(true);
        paragraphOneRunOne.setItalic(true);
        paragraphOneRunOne.setText("Font Style");
        paragraphOneRunOne.addBreak();

        //Set text Position
        XWPFRun paragraphOneRunTwo = paragraph.createRun();
        paragraphOneRunTwo.setText("Font Style two");
        paragraphOneRunTwo.setTextPosition(100);

        //Set Strike through and Font Size and Subscript
        XWPFRun paragraphOneRunThree = paragraph.createRun();
        paragraphOneRunThree.setStrike(true);
        paragraphOneRunThree.setFontSize(20);
        paragraphOneRunThree.setSubscript(
            VerticalAlign.SUBSCRIPT);
        paragraphOneRunThree.setText(" Different Font Styles");

        document.write(out);
        out.close();
        System.out.println("fontstyle.docx written successully");
    }
}
```


Save the above code as **FontStyle.java** and then compile and execute it from the command prompt as follows:

```
$javac FontStyle.java
$java FontStyle
```

It will generate a Word file named **fontstyle.docx** in your current directory and display the following output on the command prompt:

fontstyle.docx written successfully

The **fontstyle.docx** file looks as follows.



Alignment

The following code is used to set alignment to the paragraph text:

```
import java.io.File;
import java.io.FileOutputStream;
import org.apache.poi.xwpf.usermodel.ParagraphAlignment;
import org.apache.poi.xwpf.usermodel.XWPFDocument;
import org.apache.poi.xwpf.usermodel.XWPFParagraph;
import org.apache.poi.xwpf.usermodel.XWPFRun;

public class AlignParagraph
{
    public static void main(String[] args) throws Exception
    {
        //Blank Document
        XWPFDocument document= new XWPFDocument();

        //Write the Document in file system
        FileOutputStream out = new FileOutputStream(
            new File("alignparagraph.docx"));

        //create paragraph
        XWPFParagraph paragraph = document.createParagraph();

        //Set alignment paragraph to RIGHT
        paragraph.setAlignment(ParagraphAlignment.RIGHT);
        XWPFRun run=paragraph.createRun();
        run.setText("At tutorialspoint.com, we strive hard to " +
            "provide quality tutorials for self-learning " +
            "purpose in the domains of Academics, Information " +
            "Technology, Management and Computer Programming " +
            "Languages.");

        //Create Another paragraph
        paragraph=document.createParagraph();

        //Set alignment paragraph to CENTER
        paragraph.setAlignment(ParagraphAlignment.CENTER);
        run=paragraph.createRun();
        run.setText("The endeavour started by Mohtashim, an AMU " +
            "alumni, who is the founder and the managing director " +
```

```

"of Tutorials Point (I) Pvt. Ltd. He came up with the " +
"website tutorialspoint.com in year 2006 with the help" +
"of handpicked freelancers, with an array of tutorials" +
" for computer programming languages. ");
document.write(out);
out.close();
System.out.println("alignparagraph.docx written successfully");
}
}

```

Save the above code as **AlignParagraph.java** and then compile and execute it from the command prompt as follows:

```


$javac AlignParagraph.java
$java AlignParagraph

```

It will generate a Word file named **alignparagraph.docx** in your current directory and display the following output in the command prompt:

```
alignparagraph.docx written successfully
```

The **alignparagraph.docx** file looks as follows:



APACHE POI WORD - TEXT EXTRACTION

This chapter explains how to extract simple text data from a Word document using Java. In case you want to extract metadata from a Word document, make use of Apache Tika.

For .docx files, we use the class `org.apache.poi.xwpf.extractor.XWPFFWordExtractor` that extracts and returns simple data from a Word file. In the same way, we have different methodologies to extract headings, footnotes, table data, etc. from a Word file.

The following code shows how to extract simple text from a Word file:

```

import java.io.FileInputStream;
import org.apache.poi.xwpf.extractor.XWPFFWordExtractor;
import org.apache.poi.xwpf.usermodel.XWPFDocument;

public class WordExtractor
{
    public static void main(String[] args) throws Exception
    {
        XWPFDocument docx = new XWPFDocument(
            new FileInputStream("create_paragraph.docx"));
    }
}

```



```
//using XWPfWordExtractor Class
XWPfWordExtractor we = new XWPfWordExtractor(docx);
System.out.println(we.getText());
}
}
```

Save the above code as **WordExtractor.java**. Compile and execute it from the command prompt as follows:

```
$javac WordExtractor.java
$java WordExtractor
```

It will generate the following output:

```
At tutorialspoint.com, we strive hard to provide quality tutorials for self-learning
purpose in the domains of Academics, Information Technology, Management and Computer
Programming Languages.
```

```
Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js
```