

# C LIBRARY FUNCTION - STRTOL

[http://www.tutorialspoint.com/c\\_standard\\_library/c\\_function\\_sttol.htm](http://www.tutorialspoint.com/c_standard_library/c_function_sttol.htm)

Copyright © tutorialspoint.com

## Description

The C library function **long int strtol(const char \* str, char \*\* endptr, int base)** converts the initial part of the string in **str** to a **long int** value according to the given **base**, which must be between 2 and 36 inclusive, or be the special value 0.

## Declaration

Following is the declaration for strtol function.

```
long int strtol(const char *str, char **endptr, int base)
```

## Parameters

- **str** -- This is the string containing the representation of an integral number.
- **endptr** -- This is the reference to an object of type **char\***, whose value is set by the function to the next character in **str** after the numerical value.
- **base** -- This is the base, which must be between 2 and 36 inclusive, or be the special value 0.

## Return Value

This function returns the converted integral number as a **long int** value, else zero value is returned.

## Example

The following example shows the usage of strtol function.

```
#include <stdio.h>
#include <stdlib.h>

int main()
{
    char str[30] = "2030300 This is test";
    char *ptr;
    long ret;

    ret = strtol(str, &ptr, 10);
    printf("The number(unsigned long integer) is %ld\n", ret);
    printf("String part is |%s|", ptr);

    return(0);
}
```

Let us compile and run the above program that will produce the following result:

```
The number(unsigned long integer) is 2030300
String part is | This is test|
```

Loading [MathJax]/jax/output/HTML-CSS/jax.js