

Description

The *cursor* property is used in audio devices to play a sound after an element.

Possible Values

The table that follows shows possible values for the cursor property –

Value	Description
auto	Shape of the cursor depends on the context area it is over. For example an I over text, a hand over a link, and so on...
crosshair	A crosshair or plus sign
default	An arrow
pointer	A pointing hand <i>in IE4 this value is hand</i>
move	The I bar
e-resize	The cursor indicates that an edge of a box is to be moved right <i>east</i>
ne-resize	The cursor indicates that an edge of a box is to be moved up and right <i>north/east</i>
nw-resize	The cursor indicates that an edge of a box is to be moved up and left <i>north/west</i>
n-resize	The cursor indicates that an edge of a box is to be moved up <i>north</i>
se-resize	The cursor indicates that an edge of a box is to be moved down and right <i>south/east</i>
sw-resize	The cursor indicates that an edge of a box is to be moved down and left <i>south/west</i>
s-resize	The cursor indicates that an edge of a box is to be moved down <i>south</i>
w-resize	The cursor indicates that an edge of a box is to be moved left <i>west</i>
text	The I bar
wait	An hour glass
help	A question mark or balloon, ideal for use over help buttons
<url>	The source of a cursor image file

NOTE – You should try to use only these values to add helpful information for users, and in places they would expect to see that cursor. For example, using the crosshair when someone hovers over a link can confuse visitors.

Applies to

All the HTML elements.

DOM Syntax

```
object.style.cueAfter = url("music.wav");
```

Example

Here is the example –

```
<html>
  <head>
  </head>

  <body>
    <p>Move the mouse over the words to see the cursor change:</p>

    <div style="cursor:auto">Auto</div>
    <div style="cursor:crosshair">Crosshair</div>
    <div style="cursor:default">Default</div>

    <div style="cursor:pointer">Pointer</div>
    <div style="cursor:move">Move</div>
    <div style="cursor:e-resize">e-resize</div>
    <div style="cursor:ne-resize">ne-resize</div>
    <div style="cursor:nw-resize">nw-resize</div>

    <div style="cursor:n-resize">n-resize</div>
    <div style="cursor:se-resize">se-resize</div>
    <div style="cursor:sw-resize">sw-resize</div>
    <div style="cursor:s-resize">s-resize</div>
    <div style="cursor:w-resize">w-resize</div>

    <div style="cursor:text">text</div>
    <div style="cursor:wait">wait</div>
    <div style="cursor:help">help</div>
  </body>

</html>
```

This will produce following result, try to move your mouse pointer over different properties –



Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js