

EASYMOCK - CREATENICEMOCK

http://www.tutorialspoint.com/easymock/easymock_createnicemock.htm

Copyright © tutorialspoint.com

EasyMock.createNiceMock creates a mock and sets the default implementation of each method of the mock. If EasyMock.createMock is used, then invoking the mock method throws assertion error.

Syntax

```
calcService = EasyMock.createNiceMock(CalculatorService.class);
```

Example

Step 1: Create an interface called CalculatorService to provide mathematical functions.

File: CalculatorService.java

```
public interface CalculatorService {  
    public double add(double input1, double input2);  
    public double subtract(double input1, double input2);  
    public double multiply(double input1, double input2);  
    public double divide(double input1, double input2);  
}
```

Step 2: Create a JAVA class to represent MathApplication

File: MathApplication.java

```
public class MathApplication {  
    private CalculatorService calcService;  
  
    public void setCalculatorService(CalculatorService calcService){  
        this.calcService = calcService;  
    }  
  
    public double add(double input1, double input2){  
        return calcService.add(input1, input2);  
    }  
  
    public double subtract(double input1, double input2){  
        return calcService.subtract(input1, input2);  
    }  
  
    public double multiply(double input1, double input2){  
        return calcService.multiply(input1, input2);  
    }  
  
    public double divide(double input1, double input2){  
        return calcService.divide(input1, input2);  
    }  
}
```

Step 3: Test the MathApplication class

Let's test the MathApplication class, by injecting in it a mock of calculatorService. Mock will be created by EasyMock.

Here we've added one mock method call, add, via expect. However during testing, we've called subtract and other methods as well. When we create a mock object using EasyMock.createNiceMock, the default implementation with default values are available.

File: MathApplicationTester.java

```
import org.easymock.EasyMock;
```

```

import org.easymock.EasyMockRunner;

import org.junit.Assert;
import org.junit.Before;
import org.junit.Test;
import org.junit.runner.RunWith;

@RunWith(EasyMockRunner.class)
public class MathApplicationTester {

    private MathApplication mathApplication;

    private CalculatorService calcService;

    @Before
    public void setUp(){
        mathApplication = new MathApplication();
        calcService = EasyMock.createNiceMock(CalculatorService.class);
        mathApplication.setCalculatorService(calcService);
    }

    @Test
    public void testCalcService(){

        //add the behavior to add numbers
        EasyMock.expect(calcService.add(20.0,10.0)).andReturn(30.0);

        //activate the mock
        EasyMock.replay(calcService);

        //test the add functionality
        Assert.assertEquals(mathApplication.add(20.0, 10.0),30.0,0);

        //test the subtract functionality
        Assert.assertEquals(mathApplication.subtract(20.0, 10.0),0.0,0);

        //test the multiply functionality
        Assert.assertEquals(mathApplication.divide(20.0, 10.0),0.0,0);

        //test the divide functionality
        Assert.assertEquals(mathApplication.multiply(20.0, 10.0),0.0,0);

        //verify call to calcService is made or not
        EasyMock.verify(calcService);
    }
}

```

Step 4: Execute test cases

Create a java class file named TestRunner in **C:\> EasyMock_WORKSPACE** to execute Test cases.

File: TestRunner.java

```

import org.junit.runner.JUnitCore;
import org.junit.runner.Result;
import org.junit.runner.notification.Failure;

public class TestRunner {
    public static void main(String[] args) {
        Result result = JUnitCore.runClasses(MathApplicationTester.class);

        for (Failure failure : result.getFailures()) {
            System.out.println(failure.toString());
        }

        System.out.println(result.wasSuccessful());
    }
}

```

Step 5: Verify the Result

Compile the classes using javac compiler as follows:

```
C:\EasyMock_WORKSPACE>javac MathApplicationTester.java
```

Now run the Test Runner to see the result:

```
C:\EasyMock_WORKSPACE>java TestRunner
```

Verify the output.

```
true
```

```
Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js
```