

# HTML BUTTON TAG

[http://www.tutorialspoint.com/html/html\\_button\\_tag.htm](http://www.tutorialspoint.com/html/html_button_tag.htm)

Copyright © tutorialspoint.com

## Description

The HTML <button> tag is used for creating a button within HTML form. You can also use <input> tag to create similar buttons.

## Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML Button Tag</title>
</head>
<body>
<form>
<button name="button" value="OK" type="button">Click Me</button>
</form>
</body>
</html>
```

This will produce following result:

## Global Attributes

This tag supports all the global attributes described in - [HTML Attribute Reference](#)

## Specific Attributes

The HTML <button> tag also supports following additional attributes:

Attribute	Value	Description
autofocus	autofocus	Specifies that the button should have input focus when the page loads.
disabled	disabled	Specifies the button is disabled.
form	form_id	Specifies the forms to which button belongs.
formaction	URL	Specifies the link where the form submits.
formenctype	application multipart/form- data text/plain	Specifies how the form data is encoded before sending it to server.
formmethod	get post	Specifies how to send form data.
formnovalidate	formnovalidate	Specifies that the form data should not be validated.
formtarget	_blank _self _parent _top	Specifies where the response should be validated.
name	name	Specifies the button name.
type	button reset	Specifies the button type.

	submit	
value	text	Specifies button's initial value.

## Event Attributes

This tag supports all the event attributes described in - [HTML Events Reference](#)

## Browser Support

Chrome	Firefox	IE	Opera	Safari
Yes	Yes	Yes	Yes	Yes