HTML <OPTGROUP> TAG

 Copyright © tutorialspoint.com

Description

The HTML <optgroup> tag is used for grouping related options within your select list. This makes it easier for users to comprehend their choices when looking at a large list.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML optgroup Tag</title>
</head>
<body>
<select>
<optgroup label="India">
  <option value ="mumbai">Mumbai</option>
  <option value ="delhi">Delhi</option>
</optgroup>
<optgroup label="USA">
  <option value ="florida">Florida</option>
  <option value ="newyork">New York</option>
</optgroup>
</select>
</body>
</html>
```

This will produce following result:

Mumbai

Global Attributes

This tag supports all the global attributes described in - **HTML Attribute Reference**

Specific Attributes

The HTML <optgroup> tag also supports following additional attributes:

Attribute	Value	Description
disabled	disabled	Disables the input control. The button won't accept changes from the user. It also cannot receive focus and will be skipped when tabbing.
label	text	Defines a label to use when using <optgroup>.

Event Attributes

This tag supports all the event attributes described in - **HTML Events Reference**

Browser Support

Chrome	Firefox	IE	Opera	Safari	Android
Yes	Yes	Yes	Yes	Yes	Yes