Copyright © tutorialspoint.com

Description

The HTML <select> tag is used within a form for defining a select list.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML select Tag</title>
</head>
<body>
<form action="/cgi-bin/dropdown.cgi" method="post">
<select name="dropdown">
<option value="Data Structures" selected>Data Structures</option>
<option value="Data Mining">Data Mining</option>
</select>
<input type="submit" value="Submit" />
</form>
</body>
</html>
```

This will produce following result:

Data Structures

Global Attributes

This tag supports all the global attributes described in - HTML Attribute Reference

Specific Attributes

The HTML <select> tag also supports following additional attributes:

Attribute	Value	Description
autofocus	autofocus	Specifies that on page load the drop-down list should automatically get focus.
disabled	disabled	Disables the input control. The button won't accept changes from the user. It also cannot receive focus and will be skipped when tabbing.
form	form_id	Specifies one or more forms.
multiple	multiple	When set, it specifies that multiple items can be selected at a time
name	name	Assigns a name to the input control.s
required	required	Before submitting the form the user is required to select a value, else it won't proceed ahead.
size	number	Defines the number of visible items in the drop-down list

Event Attributes

This tag supports all the event attributes described in - $\underline{\textbf{HTML Events Reference}}$

Browser Support

Chrome	Firefox	IE	Opera	Safari	Android
Yes	Yes	Yes	Yes	Yes	Yes