

HTML <TD> TAG

http://www.tutorialspoint.com/html/html_td_tag.htm

Copyright © tutorialspoint.com

Description

The HTML <td> tag is used for specifying a cell or table data within a table.

Example

```
<!DOCTYPE html>
<html>
<head>
<title>HTML td Tag</title>
</head>
<body>
<table border="1">
  <tr>
    <th>Subject</th>
    <th>Topic</th>
  </tr>
  <tr>
    <td>Java</td>
    <td>Threading</td>
  </tr>
  <tr>
    <td>C++</td>
    <td>Virtual Functions</td>
  </tr>
  <tr>
    <td>Linux</td>
    <td>File Systems</td>
  </tr>
</table>
</body>
</html>
```

This will produce following result:

Subject	Topic
Java	Threading
C++	Virtual Functions
Linux	File Systems

Global Attributes

This tag supports all the global attributes described in - [HTML Attribute Reference](#)

Specific Attributes

The HTML <td> tag also supports following additional attributes:

Attribute	Value	Description
abbr	abbreviated_text	<i>Deprecated</i> -Specifies an abbreviated version of the content in a cell.
align	right	<i>Deprecated</i> -Visual alignment.

	left center justify char	
axis	name	<i>Deprecated</i> -Specifies a category for this td. This can potentially be used to perform queries against the table data and can be beneficial in the context of a speech browser.
bgcolor	rgbx, x, x #hexcode colorname	<i>Deprecated</i> -Specifies the background color of the table cell.
char	character	<i>Deprecated</i> -Specifies which character to align text on. Used when align="char"
charoff	pixels or %	<i>Deprecated</i> -Specifies an alignment offset <i>either in pixels or percentage value</i> against the first character as specified with the char attribute. Used when align="char"
colspan	number	Specifies the number of columns the current cell spans across.
header	id	Specifies a space-separated list of header cells that contain information about this cell. The value needs to correspond with the id of the header cell <i>which is set using the id attribute</i> . This attribute is useful for non-visual browsers.
height	pixels	<i>Deprecated</i> -Specifies the height of the table cell.
nowrap	nowrap	<i>Deprecated</i> -Prevents text from automatically wrapping.
rowspan	numbers	Specifies the number of rows the current cell spans across.
scope	col colgroup< row rowgroup	<i>Deprecated</i> -This attribute is used on header cells and specifies the cells that will use this header's information.
valign	top middle bottom baseline	<i>Deprecated</i> -Vertical alignment.
width	pixels or %	<i>Deprecated</i> -Specifies the width of the table cell

Event Attributes

This tag supports all the event attributes described in - [HTML Events Reference](#)

Browser Support

Chrome	Firefox	IE	Opera	Safari	Android
Yes	Yes	Yes	Yes	Yes	Yes