

JAVA.LANG.CHARACTER.ISUPPERCASE METHOD

http://www.tutorialspoint.com/java/lang/character_isuppercase_codepoint.htm

Copyright © tutorialspoint.com

Description

The **java.lang.Character.isUpperCase** method determines if the specified character *Unicode code point* is an uppercase character.

A character is uppercase if its general category type, provided by *getTypeCodePoint*, is `UPPERCASE_LETTER`, or it has contributory property `Other_Uppercase` as defined by the Unicode Standard.

Declaration

Following is the declaration for **java.lang.Character.isUpperCase** method

```
public static boolean isUpperCase(int codePoint)
```

Parameters

- **codePoint** - the character *Unicode code point* to be tested

Return Value

This method returns true if the character is uppercase, false otherwise.

Exception

- NA

Example

The following example shows the usage of `lang.Character.isUpperCase` method.

```
package com.tutorialspoint;

import java.lang.*;

public class CharacterDemo {

    public static void main(String[] args) {

        // create 2 int primitives cp1, cp2
        int cp1, cp2;

        // assign values to cp1, cp2
        cp1 = 0x004a; // represents J
        cp2 = 0x0071; // represents x

        // create 2 boolean primitives b1, b2
        boolean b1, b2;

        // check if cp1, cp2 are uppercase and assign results to b1, b2
        b1 = Character.isUpperCase(cp1);
        b2 = Character.isUpperCase(cp2);

        String str1 = "cp1 is uppercase character is " + b1;
        String str2 = "cp2 is uppercase character is " + b2;

        // print b1, b2 values
        System.out.println( str1 );
        System.out.println( str2 );
    }
}
```

Let us compile and run the above program, this will produce the following result:

```
cp1 is uppercase character is true  
cp2 is uppercase character is false
```

Loading [Mathjax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js