

JAVA.LANG.LONG.TOSTRING METHOD

http://www.tutorialspoint.com/java/lang/long_tostring_long_radix.htm

Copyright © tutorialspoint.com

Description

The **java.lang.Long.toString***longi, intradix* method returns a string representation of the first argument **i** in the radix specified by the second argument **radix**. If the radix is smaller than Character.MIN_RADIX or larger than Character.MAX_RADIX, then the radix 10 is used instead. The following ASCII characters are used as digits: **0123456789abcdefghijklmnopqrstuvwxyz**

Declaration

Following is the declaration for **java.lang.Long.toString** method

```
public static String toString(long i, int radix)
```

Parameters

- **i** -- This is a long to be converted.
- **radix** -- This is the radix to use in the string representation.

Return Value

This method returns a string representation of the argument in the specified radix.

Exception

- **NA**

Example

The following example shows the usage of java.lang.Long.toString method.

```
package com.tutorialspoint;

import java.lang.*;

public class LongDemo {

    public static void main(String[] args) {

        Long l = new Long(5);

        // returns a string representation of the specified long with radix 10
        String retval = l.toString(87630, 10);
        System.out.println("Value = " + retval);

        // returns a string representation of the specified long with radix 16
        retval = l.toString(87630, 16);
        System.out.println("Value = " + retval);

        // returns a string representation of the specified long with radix 8
        retval = l.toString(87630, 8);
        System.out.println("Value = " + retval);
    }
}
```

Let us compile and run the above program, this will produce the following result:

```
Value = 87630
Value = 1564e
Value = 253116
```

