

JAVA.LANG.PROCESSBUILDER.COMMAND METHOD

http://www.tutorialspoint.com/java/lang/processbuilder_command_string.htm

Copyright © tutorialspoint.com

Description

The **java.lang.ProcessBuilder.commandString...command** method Sets this process builder's operating system program and arguments. This is a convenience method that sets the command to a string list containing the same strings as the command array, in the same order. It is not checked whether command corresponds to a valid operating system command.

Declaration

Following is the declaration for **java.lang.ProcessBuilder.command** method

```
public ProcessBuilder command(String... command)
```

Parameters

- **command** -- A string array containing the program and its arguments

Return Value

This method returns this process builder

Exception

- NA

Example

The following example shows the usage of lang.ProcessBuilder.command method.

```
package com.tutorialspoint;

public class ProcessBuilderDemo {

    public static void main(String[] args) {

        // create a new list of arguments for our process
        String[] list = {"notepad.exe", "test.txt"};

        // create the process builder
        ProcessBuilder pb = new ProcessBuilder(list);

        // set the command list
        pb.command(list);

        // print the new command list
        System.out.println("'" + pb.command());
    }
}
```

Let us compile and run the above program, this will produce the following result:

```
[notepad.exe, test.txt]
```

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js