

JAVA.LANG.STRINGBUILDER.DELETE METHOD

http://www.tutorialspoint.com/java/lang/stringbuilder_delete.htm

Copyright © tutorialspoint.com

Description

The **java.lang.StringBuilder.delete** method removes the characters in a substring of this sequence.

The substring begins at the specified **start** and extends to the character at index **end - 1** or to the **end** of the sequence if no such character exists. If **start** is equal to **end**, no changes are made.

Declaration

Following is the declaration for **java.lang.StringBuilder.delete** method

```
public StringBuilder delete(int start, int end)
```

Parameters

- **start** -- This is the beginning index, inclusive.
- **end** -- This is the ending index, exclusive.

Return Value

This method returns this object.

Exception

- **StringIndexOutOfBoundsException** -- if start is negative, greater than length, or greater than end.

Example

The following example shows the usage of java.lang.StringBuilder.delete method.

```
package com.tutorialspoint;

import java.lang.*;

public class StringBuilderDemo {

    public static void main(String[] args) {

        StringBuilder str = new StringBuilder("Java lang package");
        System.out.println("string = " + str);

        // deleting characters from index 4 to index 9
        str.delete(4, 9);
        System.out.println("After deletion = " + str);
    }
}
```

Let us compile and run the above program, this will produce the following result:

```
string = Java lang package
After deletion = Java package
```

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js