

JAVA.LANG.STRINGBUILDER.INSERT METHOD

http://www.tutorialspoint.com/java/lang/stringbuilder_insert_float.htm

Copyright © tutorialspoint.com

Description

The **java.lang.StringBuilder.insertintooffset, floatf** method inserts the string representation of the **float** argument into this sequence.

The **offset** argument must be greater than or equal to 0, and less than or equal to the length of this sequence.

Declaration

Following is the declaration for **java.lang.StringBuilder.insert** method

```
public StringBuilder insert(int offset, float f)
```

Parameters

- **offset** -- This is the offset.
- **f** -- This is the value of float.

Return Value

This method returns a reference to this object.

Exception

- **StringIndexOutOfBoundsException** -- if the offset is invalid.

Example

The following example shows the usage of java.lang.StringBuilder.insert method.

```
package com.tutorialspoint;

import java.lang.*;

public class StringBuilderDemo {

    public static void main(String[] args) {

        StringBuilder str = new StringBuilder("zyxwvut");
        System.out.println("string = " + str);

        // insert float value at offset 3
        str.insert(3, 53.2f);

        // prints StringBuilder after insertion
        System.out.print("After insertion = ");
        System.out.println(str.toString());
    }
}
```

Let us compile and run the above program, this will produce the following result:

```
string = zyxwvut
After insertion = zvx53.2wvut
```

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js