

JAVA.UTIL.BITSET.SET METHOD

http://www.tutorialspoint.com/java/util/bitset_set_bitindex_value.htm

Copyright © tutorialspoint.com

Description

The **java.util.BitSet.set**(*int bitIndex*, *boolean value*) method sets the bit at the specified index to the specified value.

Declaration

Following is the declaration for **java.util.BitSet.set** method

```
public void set(int bitIndex, boolean value)
```

Parameters

- **bitIndex** -- a bit index.
- **value** -- a boolean value to set.

Return Value

This method does not return a value.

Exception

- **IndexOutOfBoundsException** -- if the specified index is negative.

Example

The following example shows the usage of java.util.BitSet.set method.

```
package com.tutorialspoint;

import java.util.*;

public class BitSetDemo {

    public static void main(String[] args) {

        // create 2 bitsets
        BitSet bitset1 = new BitSet(8);
        BitSet bitset2 = new BitSet(8);

        // assign values to bitset1
        bitset1.set(0);
        bitset1.set(1);
        bitset1.set(2);
        bitset1.set(3);
        bitset1.set(4);
        bitset1.set(5);

        // assign values to bitset2
        bitset2.set(2);
        bitset2.set(4);
        bitset2.set(6);
        bitset2.set(8);
        bitset2.set(10);

        // print the sets
        System.out.println("Bitset1:" + bitset1);
        System.out.println("Bitset2:" + bitset2);

        // set more values
```

```
bitset1.set(1, false);
bitset1.set(5, true);
bitset1.set(10, true);
bitset2.set(1, false);
bitset2.set(5, true);
bitset2.set(10, true);

// print the sets
System.out.println("Bitset1:" + bitset1);
System.out.println("Bitset2:" + bitset2);
}
```

Let us compile and run the above program, this will produce the following result:

```
Bitset1:{0, 1, 2, 3, 4, 5}
Bitset2:{2, 4, 6, 8, 10}
Bitset1:{0, 2, 3, 4, 5, 10}
Bitset2:{2, 4, 5, 6, 8, 10}
```

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js