

JAVA.UTIL.CALENDAR.COMPLETE METHOD

http://www.tutorialspoint.com/java/util/calendar_complete.htm

Copyright © tutorialspoint.com

Description

The **java.util.Calendar.complete** method fills in any unset fields in the calendar fields. First, the `computeTime` method is called if the time value *millisecondoffsetfromtheEpoch* has not been calculated from calendar field values. Then, the `computeFields` method is called to calculate all calendar field values.

Declaration

Following is the declaration for **java.util.Calendar.complete** method

```
protected void complete()
```

Parameters

- NA

Return Value

This method does not return any value.

Exception

- NA

Example

The following example shows the usage of `java.util.Calendar.complete` method.

```
package com.tutorialspoint;

import java.util.*;

public class CalendarDemo extends GregorianCalendar {

    public static void main(String[] args) {

        // create a new calendar
        CalendarDemo cal = new CalendarDemo();

        // print the current date
        System.out.println("The current date is : " + cal.getTime());

        // clear the calendar
        cal.clear();

        // set a new year and call complete()
        cal.set(GregorianCalendar.YEAR, 1998);
        cal.complete();

        // print the current date
        System.out.println("New date is : " + cal.getTime());

    }
}
```

Let us compile and run the above program, this will produce the following result:

```
The current date is : Thu Jun 21 15:32:48 EEST 2012
New date is : Thu Jan 01 00:00:00 EET 1998
```

