

JAVA.UTIL.CALENDAR.SETTIMEINMILLIS METHOD

http://www.tutorialspoint.com/java/util/calendar_settimeinmillis.htm

Copyright © tutorialspoint.com

Description

The **java.util.Calendar.setTimeInMillis** method sets Calendar's current time from the given long value.

Declaration

Following is the declaration for **java.util.Calendar.setTimeInMillis** method

```
public void setTimeInMillis(long millis)
```

Parameters

- **millis** -- the new time in UTC milliseconds from the epoch.

Return Value

This method does not return a value.

Exception

- NA

Example

The following example shows the usage of java.util.calendar.setTimeInMillis method.

```
package com.tutorialspoint;

import java.util.*;

public class CalendarDemo {

    public static void main(String[] args) {

        // create a calendar
        Calendar cal = Calendar.getInstance();

        // get the time in milliseconds
        System.out.println("Current time is :" + cal.getTime());

        // set time to 5000 ms after january 1 1970
        cal.setTimeInMillis(5000);

        // print the new time
        System.out.println("After setting Time: " + cal.getTime());
    }
}
```

Let us compile and run the above program, this will produce the following result:

```
Current time is :Wed May 02 20:36:23 EEST 2012
After setting Time: Thu Jan 01 02:00:05 EET 1970
Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js
```