

JAVA.UTIL.SIMPLETIMEZONE.SETSTARTYEAR METHOD

http://www.tutorialspoint.com/java/util/simpletimezone_setstartyear.htm

Copyright © tutorialspoint.com

Description

The **setStartYear***int***year** method is used to set the daylight saving time starting year.

Declaration

Following is the declaration for **java.util.SimpleTimeZone.setStartYear** method.

```
public void setStartYear(int year)
```

Parameters

- **year** -- The daylight saving starting year.

Return Value

- NA

Exception

- NA

Example

The following example shows the usage of `java.util.SimpleTimeZone.setStartYear`

```
package com.tutorialspoint;

import java.util.*;

public class SimpleTimeZoneDemo {
    public static void main( String args[] ){
        // create simple time zone object
        SimpleTimeZone stobj = new SimpleTimeZone(820,"US");

        // checking initial value
        System.out.println("Initial value: " + stobj);

        // setting start year
        stobj.setStartYear(2008);

        // checking the new value
        System.out.println("Final value : " + stobj);
    }
}
```

Let us compile and run the above program, this will produce the following result.

```
Initial value: java.util.SimpleTimeZone[id=US,offset=820,dstSavings=3600000,
useDaylight=false,startYear=0,startMode=0,startMonth=0,startDay=0,
startDayOfWeek=0,startTime=0,startTimeMode=0,endMode=0,endMonth=0,
endDay=0,endDayOfWeek=0,endTime=0,endTimeMode=0]
```

```
Final value : java.util.SimpleTimeZone[id=US,offset=820,dstSavings=3600000,
useDaylight=false,startYear=2008,startMode=0,startMonth=0,startDay=0,
startDayOfWeek=0,startTime=0,startTimeMode=0,endMode=0,endMonth=0,
endDay=0,endDayOfWeek=0,endTime=0,endTimeMode=0]
```

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js