

JAVA.UTIL.UUID.FROMSTRING METHOD

http://www.tutorialspoint.com/java/util/uuid_fromstring.htm

Copyright © tutorialspoint.com

Description

The **fromString***String**name* method is used to create a UUID from the string standard representation as described in the **toString** method.

Declaration

Following is the declaration for **java.util.UUID.fromString** method.

```
public static UUID fromString(String name)
```

Parameters

- **name** -- This is a string that specifies a UUID.

Return Value

The method call returns a UUID with the specified value.

Exception

- **IllegalArgumentException** -- This exception is thrown if the name does not conform to the string representation as described in **toString**.

Example

The following example shows the usage of **java.util.UUID.fromString**

```
package com.tutorialspoint;

import java.util.*;

public class UUIDDemo {
    public static void main(String[] args) {
        // creating UUID
        UUID uid = UUID.fromString("38400000-8cf0-11bd-b23e-10b96e4ef00d");

        // checking UUID value
        System.out.println("UUID value is: "+uid);
    }
}
```

Let us compile and run the above program, this will produce the following result.

```
UUID value is: 38400000-8cf0-11bd-b23e-10b96e4ef00d
Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js
```