

JSF - ENVIRONMENT SETUP

http://www.tutorialspoint.com/jsf/jsf_environment_setup.htm

Copyright © tutorialspoint.com

This tutorial will guide you on how to prepare a development environment to start your work with JSF Framework. This tutorial will also teach you how to setup JDK, Eclipse, Maven, and Tomcat on your machine before you setup JSF Framework:

System Requirement

JSF requires JDK 1.5 or higher so the very first requirement is to have JDK installed in your machine.

JDK	1.5 or above.
Memory	no minimum requirement.
Disk Space	no minimum requirement.
Operating System	no minimum requirement.

Follow the given steps to setup your environment to start with JSF application development.

Step 1 - Verify Java installation on your machine

Now open console and execute the following **java** command.

OS	Task	Command
Windows	Open Command Console	c:\> java -version
Linux	Open Command Terminal	\$ java -version
Mac	Open Terminal	machine:~ joseph\$ java -version

Let's verify the output for all the operating systems:

OS	Generated Output
Windows	java version "1.6.0_21" Java™ SE Runtime Environment build1.6.0_21 – b07 Java HotSpot™ Client VM build17.0 – b17, mixedmode, sharing
Linux	java version "1.6.0_21" Java™ SE Runtime Environment build1.6.0_21 – b07 Java HotSpot™ Client VM build17.0 – b17, mixedmode, sharing
Mac	java version "1.6.0_21" Java™ SE Runtime Environment build1.6.0_21 – b07 Java HotSpot™64-Bit Server VM build17.0 – b17, mixedmode, sharing

Step 2 - Setup Java Development Kit *JDK*:

If you do not have Java installed then you can install the Java Software Development Kit *SDK* from Oracle's Java site: [Java SE Downloads](#). You will find instructions for installing JDK in downloaded files, follow the given instructions to install and configure the setup. Finally set `PATH` and `JAVA_HOME` environment variables to refer to the directory that contains java and javac, typically `java_install_dir/bin` and `java_install_dir` respectively.

Set the **JAVA_HOME** environment variable to point to the base directory location where Java is installed on your machine. For example

OS	Output
Windows	Set the environment variable <code>JAVA_HOME</code> to <code>C:\Program Files\Java\jdk1.6.0_21</code>
Linux	<code>export JAVA_HOME=/usr/local/java-current</code>
Mac	<code>export JAVA_HOME=/Library/Java/Home</code>

Append Java compiler location to System Path.

OS	Output
Windows	Append the string <code>;%JAVA_HOME%\bin</code> to the end of the system variable, <code>Path</code> .
Linux	<code>export PATH=PATH:JAVA_HOME/bin/</code>
Mac	not required

Alternatively, if you use an Integrated Development Environment *IDE* like Borland JBuilder, Eclipse, IntelliJ IDEA, or Sun ONE Studio, compile and run a simple program to confirm that the IDE knows where you installed Java, otherwise do proper setup as given document of the IDE.

Step 3 - Setup Eclipse IDE

All the examples in this tutorial have been written using Eclipse IDE. So I would suggest you should have latest version of Eclipse installed on your machine based on your operating system.

To install Eclipse IDE, download the latest Eclipse binaries with WTP support from <http://www.eclipse.org/downloads/>. Once you downloaded the installation, unpack the binary distribution into a convenient location. For example in `C:\eclipse` on windows, or `/usr/local/eclipse` on Linux/Unix and finally set `PATH` variable appropriately.


Eclipse can be started by executing the following commands on windows machine, or you can simply double click on `eclipse.exe`


```
%C:\eclipse\eclipse.exe
```

Eclipse can be started by executing the following commands on Unix *Solaris*, *Linux*, *etc.* machine:

```
$/usr/local/eclipse/eclipse
```

After a successful startup, if everything is fine then it should display following result:





***Note:** Install m2eclipse plugin to eclipse using following eclipse software update site

m2eclipse Plugin - <http://m2eclipse.sonatype.org/update/>.

This plugin enables developers to run maven commands within eclipse with embedded/external maven installation.

Step 4: Download Maven archive

Download Maven 2.2.1 from <http://maven.apache.org/download.html>

OS	Archive name
Windows	apache-maven-2.0.11-bin.zip
Linux	apache-maven-2.0.11-bin.tar.gz
Mac	apache-maven-2.0.11-bin.tar.gz

Step 5: Extract the Maven archive

Extract the archive, to the directory you wish to install Maven 2.2.1. The subdirectory apache-maven-2.2.1 will be created from the archive.

OS	Location <i>canbedifferentbasedonyourinstallation</i>
Windows	C:\Program Files\Apache Software Foundation\apache-maven-2.2.1
Linux	/usr/local/apache-maven
Mac	/usr/local/apache-maven

Step 6: Set Maven environment variables

Add M2_HOME, M2, MAVEN_OPTS to environment variables.

OS	Output
Windows	Set the environment variables using system properties. <i>M2_HOME=C:\Program Files\Apache Software Foundation\apache-maven-2.2.1</i> <i>M2=%M2_HOME%\bin</i> <i>MAVEN_OPTS=-Xms256m -Xmx512m</i>
Linux	Open command terminal and set environment variables. <i>export M2_HOME=/usr/local/apache-maven/apache-maven-2.2.1</i> <i>export M2=%M2_HOME%\bin</i> <i>export MAVEN_OPTS=-Xms256m -Xmx512m</i>
Mac	Open command terminal and set environment variables. <i>export M2_HOME=/usr/local/apache-maven/apache-maven-2.2.1</i> <i>export M2=%M2_HOME%\bin</i> <i>export MAVEN_OPTS=-Xms256m -Xmx512m</i>

Step 7: Add Maven bin directory location to system path

Now append M2 variable to System Path

OS	Output
Windows	Append the string ;%M2% to the end of the system variable, Path.
Linux	<i>export PATH=M2: PATH</i>
Mac	<i>export PATH=M2: PATH</i>

Step 8: Verify Maven installation

Now open console, execute the following **mvn** command.

OS	Task	Command
Windows	Open Command Console	<i>c:\> mvn --version</i>
Linux	Open Command Terminal	<i>\$ mvn --version</i>
Mac	Open Terminal	<i>machine:~ joseph\$ mvn --version</i>

Finally, verify the output of the above commands, which should be something as follows:

OS	Output
Windows	Apache Maven 2.2.1 r801777; 2009 – 08 – 0700:46:01 + 0530

	Java version: 1.6.0_21
	Java home: C:\Program Files\Java\jdk1.6.0_21\jre
Linux	Apache Maven 2.2.1 r801777; 2009 - 08 - 0700:46:01 + 0530
	Java version: 1.6.0_21
	Java home: C:\Program Files\Java\jdk1.6.0_21\jre
Mac	Apache Maven 2.2.1 r801777; 2009 - 08 - 0700:46:01 + 0530
	Java version: 1.6.0_21
	Java home: C:\Program Files\Java\jdk1.6.0_21\jre

Step 9: Setup Apache Tomcat:

You can download the latest version of Tomcat from <http://tomcat.apache.org/>. Once you downloaded the installation, unpack the binary distribution into a convenient location. For example in C:\apache-tomcat-6.0.33 on windows, or /usr/local/apache-tomcat-6.0.33 on Linux/Unix and set CATALINA_HOME environment variable pointing to the installation locations.

Tomcat can be started by executing the following commands on windows machine, or you can simply double click on startup.bat

```
%CATALINA_HOME%\bin\startup.bat

or

C:\apache-tomcat-6.0.33\bin\startup.bat
```


Tomcat can be started by executing the following commands on Unix *Solaris, Linux, etc.* machine:

```
$CATALINA_HOME/bin/startup.sh

or

/usr/local/apache-tomcat-6.0.33/bin/startup.sh
```

After a successful startup, the default web applications included with Tomcat will be available by visiting **http://localhost:8080/**. If everything is fine then it should display following result:





Further information about configuring and running Tomcat can be found in the documentation included here, as well as on the Tomcat web site: <http://tomcat.apache.org>

Tomcat can be stopped by executing the following commands on windows machine:

```
%CATALINA_HOME%\bin\shutdown
or
C:\apache-tomcat-5.5.29\bin\shutdown
```

Tomcat can be stopped by executing the following commands on Unix *Solaris, Linux, etc.* machine:

```
$CATALINA_HOME/bin/shutdown.sh
or
/usr/local/apache-tomcat-5.5.29/bin/shutdown.sh
```

Loading [MathJax]/jax/output/HTML-CSS/jax.js