

JSTL CORE <FMT:SETBUNDLE> TAG

http://www.tutorialspoint.com/jsp/jstl_format_setbundle_tag.htm

Copyright © tutorialspoint.com

The <fmt:setBundle> tag is used to load a resource bundle and stores it in the named scoped variable or the bundle configuration variable.

Attribute:

The <fmt:setBundle> tag has following attributes:

Attribute	Description	Required	Default
basename	Base name of the resource bundle family to expose as a scoped or configuration variable	Yes	None
var	Name of the variable to store the new bundle	No	Replace default
scope	Scope of the variable to store the new bundle	No	Page

Example:

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt" %>
<html>
<head>
<title>JSTL fmt:setBundle Tag</title>
</head>
<body>

<fmt:setLocale value="en"/>
<fmt:setBundle basename="com.tutorialspoint.Example" var="lang"/>

<fmt:message key="count.one" bundle="${lang}"/><br/>
<fmt:message key="count.two" bundle="${lang}"/><br/>
<fmt:message key="count.three" bundle="${lang}"/><br/>

</body>
</html>
```

This would produce following result:

```
One
Two
Three
```