

JSTL CORE <FMT:TIMEZONE> TAG

http://www.tutorialspoint.com/jsp/jstl_format_timezone_tag.htm

Copyright © tutorialspoint.com

The <fmt:timeZone> tag is used to specify the time zone that all tags within its body will use.

Attribute:

The <fmt:timeZone> tag has following attributes:

Attribute	Description	Required	Default
value	Time zone to apply to the body	Yes	None

Example:

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt" %>
<html>
  <head>
    <title>JSTL fmt:timeZone Tag</title>
  </head>

  <body>
    <c:set var="now" value="<%=new java.util.Date()%>" />
    <table border="1" width="100%">
      <tr>
        <td width="100%" colspan="2" bgcolor="#0000FF">
          <p align="center">
            <b>
              <font color="#FFFFFF" size="4">Formatting:
              <fmt:formatDate value="{now}" type="both"
                timeStyle="long" dateStyle="long" />
              </font>
            </b>
          </p>
        </td>
      </tr>

      <c:forEach var="zone"
        items="<%=java.util.TimeZone.getAvailableIDs()%>">
        <tr>
          <td width="51%">
            <c:out value="{zone}" />
          </td>
          <td width="49%">
            <fmt:timeZone value="{zone}">
              <fmt:formatDate value="{now}" timeZone="{zn}"
                type="both" />
            </fmt:timeZone>
          </td>
        </tr>
      </c:forEach>
    </table>
  </body>
</html>
```

This would produce following result:



Formatting: 23 September 2010 15:09:09 GST

Etc/GMT+12	22-Sep-2010 23:09:09
Etc/GMT+11	23-Sep-2010 00:09:09

.....