

JSTL FN:CONTAINSIGNORECASE FUNCTION

http://www.tutorialspoint.com/jsp/jstl_function_containsignorecase.htm

Copyright © tutorialspoint.com

The fn:containsIgnoreCase function determines whether an input string contains a specified substring. While doing search it ignores the case.

Syntax:

The fn:containsIgnoreCase function has following syntax:

```
boolean containsIgnoreCase(java.lang.String, java.lang.String)
```

Example:

Following is the example to explain the functionality of this function:

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ taglib uri="http://java.sun.com/jsp/jstl/functions" prefix="fn" %>
<html>
<head>
<title>Using JSTL Functions</title>
</head>
<body>

<c:set var="theString" value="I am a test String"/>

<c:if test="${fn:containsIgnoreCase(theString, 'test')}">
    <p>Found test string<p>
</c:if>

<c:if test="${fn:containsIgnoreCase(theString, 'TEST')}">
    <p>Found TEST string<p>
</c:if>

</body>
</html>
```

This would produce following result:

```
Found test string
Found TEST string
```

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js