

PERL ENHOSTENT FUNCTION

http://www.tutorialspoint.com/perl/perl_endhostent.htm

Copyright © tutorialspoint.com

Description

This function tells the system you no longer expect to read entries from the hosts file using `gethostent`.

Syntax

Following is the simple syntax for this function –

```
endhostent
```

Return Value

This function does not return any value.

Example

Following is the example code showing its basic usage –

```
#!/usr/bin/perl

while( ($name, $aliases, $addrtype, $length, @addrs) = gethostent() ){
    print "Name = $name\n";
    print "Aliases = $aliases\n";
    print "Addr Type = $addrtype\n";
    print "Length = $length\n";
    print "Addrs = @addrs\n";
}

sethostent(1);

while( ($name, $aliases, $addrtype, $length, @addrs) = gethostent() ){
    print "Name = $name\n";
    print "Aliases = $aliases\n";
    print "Addr Type = $addrtype\n";
    print "Length = $length\n";
    print "Addrs = @addrs\n";
}

endhostent(); # Closes the database;
```

When above code is executed, it produces the following result –

```
Name = ip-50-62-147-141.ip.secureserver.net
Aliases = ip-50-62-147-141 localhost.secureserver.net localhost.localdomain localhost
Addr Type = 2
Length = 4
Addrs =
Name = ip-50-62-147-141.ip.secureserver.net
Aliases = ip-50-62-147-141 localhost.secureserver.net localhost.localdomain localhost
Addr Type = 2
Length = 4
Addrs =
```