

PERL ENDNETENT FUNCTION

http://www.tutorialspoint.com/perl/perl_endnetent.htm

Copyright © tutorialspoint.com

Description

This function tells the system you no longer expect to read entries from the networks list using getnetent.

Syntax

Following is the simple syntax for this function –

```
endnetent
```

Return Value

This function does not return any value.

Example

Following is the example code showing its basic usage –

```
#!/usr/bin/perl

use Socket;

while ( ($name, $aliases, $addrtype, $net) = getnetent() ){

    print "Name = $name\n";
    print "Aliases = $aliases\n";
    print "Addrtype = $addrtype\n";
    print "Net = $net\n";
}

setnetent(1); # Rewind the database;

while ( ($name, $aliases, $addrtype, $net) = getnetent() ){

    print "Name = $name\n";
    print "Aliases = $aliases\n";
    print "Addrtype = $addrtype\n";
    print "Net = $net\n";
}

endnetent(); # Closes the database;
```

When above code is executed, it produces the following result –

```
Name = default
Aliases =
Addrtype = 2
Net = 0
Name = loopback
Aliases =
Addrtype = 2
Net = 2130706432
Name = link-local
Aliases =
Addrtype = 2
Net = 2851995648
Name = default
Aliases =
Addrtype = 2
Net = 0
```

```
Name = loopback
Aliases =
Addrtype = 2
Net = 2130706432
Name = link-local
Aliases =
Addrtype = 2
Net = 2851995648
```