

A PL/SQL **record** is a data structure that can hold data items of different kinds. Records consist of different fields, similar to a row of a database table.

For example, you want to keep track of your books in a library. You might want to track the following attributes about each book like, Title, Author, Subject, Book ID. A record containing a field for each of these items allows treating a BOOK as a logical unit and allows you to organize and represent its information in a better way.

PL/SQL can handle the following types of records:

- Table-based
- Cursor-based records
- User-defined records

Table-Based Records

The %ROWTYPE attribute enables a programmer to create **table-based** and **cursor-based** records.

The following example would illustrate the concept of **table-based** records. We will be using the CUSTOMERS table we had created and used in the previous chapters:

```
DECLARE
    customer_rec customers%rowtype;
BEGIN
    SELECT * INTO customer_rec
    FROM customers
    WHERE id = 5;

    dbms_output.put_line('Customer ID: ' || customer_rec.id);
    dbms_output.put_line('Customer Name: ' || customer_rec.name);
    dbms_output.put_line('Customer Address: ' || customer_rec.address);
    dbms_output.put_line('Customer Salary: ' || customer_rec.salary);
END;
```

When the above code is executed at SQL prompt, it produces the following result:

```
Customer ID: 5
Customer Name: Hardik
Customer Address: Bhopal
Customer Salary: 9000
```

PL/SQL procedure successfully completed.

Cursor-Based Records

The following example would illustrate the concept of **cursor-based** records. We will be using the CUSTOMERS table we had created and used in the previous chapters:

```
DECLARE
    CURSOR customer_cur IS
        SELECT id, name, address
        FROM customers;
    customer_rec customer_cur%rowtype;
BEGIN
    OPEN customer_cur;
    LOOP
        FETCH customer_cur INTO customer_rec;
```

```

        EXIT WHEN customer_cur%notfound;
        DBMS_OUTPUT.put_line(customer_rec.id || ' ' || customer_rec.name);
    END LOOP;
END;
/

```

When the above code is executed at SQL prompt, it produces the following result:

```

1 Ramesh
2 Khilan
3 kaushik
4 Chaitali
5 Hardik
6 Komal

PL/SQL procedure successfully completed.

```

User-Defined Records

PL/SQL provides a user-defined record type that allows you to define different record structures. Records consist of different fields. Suppose you want to keep track of your books in a library. You might want to track the following attributes about each book:

- Title
- Author
- Subject
- Book ID

Defining a Record

The record type is defined as:

```

TYPE
type_name IS RECORD
( field_name1 datatype1 [NOT NULL] [:= DEFAULT EXPRESSION],
  field_name2 datatype2 [NOT NULL] [:= DEFAULT EXPRESSION],
  ...
  field_nameN datatypeN [NOT NULL] [:= DEFAULT EXPRESSION]);
record-name type_name;

```

Here is the way you would declare the Book record:

```

DECLARE
TYPE books IS RECORD
(title varchar(50),
 author varchar(50),
 subject varchar(100),
 book_id number);
book1 books;
book2 books;

```

Accessing Fields

To access any field of a record, we use the dot . operator. The member access operator is coded as a period between the record variable name and the field that we wish to access. Following is the example to explain usage of record:

```

DECLARE
    type books is record
        (title varchar(50),
         author varchar(50),
         subject varchar(100),
         book_id number);

```

```

book1 books;
book2 books;
BEGIN
  -- Book 1 specification
  book1.title := 'C Programming';
  book1.author := 'Nuha Ali ';
  book1.subject := 'C Programming Tutorial';
  book1.book_id := 6495407;

  -- Book 2 specification
  book2.title := 'Telecom Billing';
  book2.author := 'Zara Ali';
  book2.subject := 'Telecom Billing Tutorial';
  book2.book_id := 6495700;

  -- Print book 1 record
  dbms_output.put_line('Book 1 title : ' || book1.title);
  dbms_output.put_line('Book 1 author : ' || book1.author);
  dbms_output.put_line('Book 1 subject : ' || book1.subject);
  dbms_output.put_line('Book 1 book_id : ' || book1.book_id);

  -- Print book 2 record
  dbms_output.put_line('Book 2 title : ' || book2.title);
  dbms_output.put_line('Book 2 author : ' || book2.author);
  dbms_output.put_line('Book 2 subject : ' || book2.subject);
  dbms_output.put_line('Book 2 book_id : ' || book2.book_id);
END;
/

```

When the above code is executed at SQL prompt, it produces the following result:

```

Book 1 title : C Programming
Book 1 author : Nuha Ali
Book 1 subject : C Programming Tutorial
Book 1 book_id : 6495407
Book 2 title : Telecom Billing
Book 2 author : Zara Ali
Book 2 subject : Telecom Billing Tutorial
Book 2 book_id : 6495700

```

PL/SQL procedure successfully completed.

Records as Subprogram Parameters

You can pass a record as a subprogram parameter in very similar way as you pass any other variable. You would access the record fields in the similar way as you have accessed in the above example:

```

DECLARE
  type books is record
    (title varchar(50),
    author varchar(50),
    subject varchar(100),
    book_id number);
  book1 books;
  book2 books;

PROCEDURE printbook (book books) IS
BEGIN
  dbms_output.put_line ('Book title : ' || book.title);
  dbms_output.put_line('Book author : ' || book.author);
  dbms_output.put_line('Book subject : ' || book.subject);
  dbms_output.put_line('Book book_id : ' || book.book_id);
END;

BEGIN
  -- Book 1 specification
  book1.title := 'C Programming';

```

```

book1.author := 'Nuha Ali ';
book1.subject := 'C Programming Tutorial';
book1.book_id := 6495407;

-- Book 2 specification
book2.title := 'Telecom Billing';
book2.author := 'Zara Ali';
book2.subject := 'Telecom Billing Tutorial';
book2.book_id := 6495700;

-- Use procedure to print book info
printbook(book1);
printbook(book2);
END;
/

```

When the above code is executed at SQL prompt, it produces the following result:

```

Book title : C Programming
Book author : Nuha Ali
Book subject : C Programming Tutorial
Book book_id : 6495407
Book title : Telecom Billing
Book author : Zara Ali
Book subject : Telecom Billing Tutorial
Book book_id : 6495700

```

PL/SQL procedure successfully completed.

Loading [MathJax]/jax/output/HTML-CSS/jax.js