

UDDI API - DELETE_BINDING

http://www.tutorialspoint.com/uddi/delete_binding.htm

Copyright © tutorialspoint.com

Description : The delete_binding API call causes one or more instances of bindingTemplate data to be deleted from the UDDI registry.

Upon successful completion, a dispositionReport is returned with a single success indicator. References to bindingTemplates that are deleted as a result of this call, such as those referenced by other bindingTemplates *inhostingRedirectorelements* are not affected.

Version 2.0 Syntax

```
<delete_binding generic="2.0" xmlns="urn:uddi-org:api_v2" >
  <authInfo/>
  <bindingKey/> [<bindingKey/> .]
</delete_binding>
```

Arguments

authInfo : This required argument is an element that contains an authentication token. Authentication tokens are obtained using the get_authToken API call.

bindingKey : one or more *uuid_key* values that represent specific instances of known bindingTemplate data.

Error Returned

If any error occurs in processing this API call, a dispositionReport element will be returned to the caller within a SOAP Fault. The following error number information will be relevant:

E_invalidKeyPassed : It signifies that one of the *uuid_key* values passed did not match with any known bindingKey values. No partial results will be returned - if any bindingKey values passed are not valid or if the message contained multiple instances of a *uuid_key* value, this error will be returned.

E_authTokenExpired : It signifies that the authentication token value passed in the *authInfo* argument is no longer valid because the token has expired.

E_authTokenRequired : It signifies that the authentication token value passed in the *authInfo* argument is either missing or is not valid.

E_userMismatch : It signifies that one or more of the bindingKey values passed refers to a bindingTemplate that is not controlled by the individual associated with the authentication token.

Loading [MathJax]/jax/output/HTML-CSS/fonts/TeX/fontdata.js