

UDDI API - DELETE_TMODEL

http://www.tutorialspoint.com/uddi/delete_tModel.htm

Copyright © tutorialspoint.com

Description : The delete_tModel API call is used to logically delete one or more tModel structures. Logical deletion hides the deleted tModels from find_tModel result sets but does not physically delete it. Deleting an already deleted tModel has no effect.

Upon successful completion, a dispositionReport message is returned with a single success indicator.

Version 2.0 Syntax

```
<delete_tModel generic="2.0" xmlns="urn:uddi-org:api_v2" >
  <authInfo/>
  <tModelKey/> [<tModelKey/> .]
</delete_tModel>
```

Arguments

authInfo : This required argument is an element that contains an authentication token. Authentication tokens are obtained using the get_authToken API call.

tModelKey : one or more URN qualified uuid_key values that represent specific instances of known tModel data. All tModelKey values begin with a uuid URN qualifier
e. g. " uuid:" followed by a known tModel UUID value.

Error Returned

If any error occurs in processing this API call, a dispositionReport element will be returned to the caller within a SOAP Fault. The following error number information will be relevant:

E_invalidKeyPassed : It signifies that one of the URN qualified uuid_key values passed did not match with any known tModelKey values.

E_authTokenExpired : It signifies that the authentication token value passed in the authInfo argument is no longer valid because the token has expired.

E_authTokenRequired : It signifies that the authentication token value passed in the authInfo argument is either missing or is not valid.

E_userMismatch : It signifies that one or more of the tModelKey values passed refers to data that is not controlled by the individual who is represented by the authentication token.

Loading [MathJax]/jax/output/HTML-CSS/jax.js