# MATERIAL - HARDWARE ICONS

This chapter explains the usage of Google's *Material* Hardware icons. Assume that **custom** is the CSS class name where we defined the size and color, as shown in the example given below.

```html
<!DOCTYPE html>
<html>
    <head>
        <link href = "https://fonts.googleapis.com/icon?family=Material+Icons" rel =
"stylesheet">

        <style>
            i.custom {font-size: 2em; color: green;}
        </style>

    </head>

    <body>
        <i class = "material-icons custom">accessibility</i>
    </body>

</html>
```

The following table contains the usage and results of Google's *Material* Hardware icons. Replace the < body > tag of the above program with the code given in the table to get the respective outputs −

| Usage | Result |
|---|---|
| <i >cast</i> | *cast* |
| <i >cast_connected</i> | *cast_connected* |
| <i >computer</i> | *computer* |
| <i >desktop_mac</i> | *desktop_mac* |
| <i >desktop_windows</i> | *desktop_windows* |
| <i >developer_board</i> | *developer_board* |
| <i >device_hub</i> | *device_hub* |
| <i >dock</i> | *dock* |
| <i >gamepad</i> | *gamepad* |
| <i >headset</i> | *headset* |
| <i >headset_mic</i> | *headset_mic* |
| <i >keyboard</i> | *keyboard* |
| <i >keyboard_arrow_down</i> | *keyboard_arrow_down* |
| <i >keyboard_arrow_left</i> | *keyboard_arrow_left* |
| <i >keyboard_arrow_right</i> | *keyboard_arrow_right* |
| <i >keyboard_arrow_up</i> | *keyboard_arrow_up* |
| <i >keyboard_backspace</i> | *keyboard_backspace* |

| | |
|---|---|
| <i >keyboard_capslock</i> | *keyboard_capslock* |
| <i >keyboard_hide</i> | *keyboard_hide* |
| <i >keyboard_return</i> | *keyboard_return* |
| <i >keyboard_tab</i> | *keyboard_tab* |
| <i >keyboard_voice</i> | *keyboard_voice* |
| <i >laptop</i> | *laptop* |
| <i >laptop_chromebook</i> | *laptop_chromebook* |
| <i >laptop_mac</i> | *laptop_mac* |
| <i >laptop_windows</i> | *laptop_windows* |
| <i >memory</i> | *memory* |
| <i >mouse</i> | *mouse* |
| <i >phone_android</i> | *phone_android* |
| <i >phone_iphone</i> | *phone_iphone* |
| <i >phonelink</i> | *phonelink* |
| <i >phonelink_off</i> | *phonelink_off* |
| <i >power_input</i> | *power_input* |
| <i >router</i> | *router* |
| <i >scanner</i> | *scanner* |
| <i >security</i> | *security* |
| <i >sim_card</i> | *sim_card* |
| <i >smartphone</i> | *smartphone* |
| <i >speaker</i> | *speaker* |
| <i >speaker_group</i> | *speaker_group* |
| <i >tablet</i> | *tablet* |
| <i >tablet_android</i> | *tablet_android* |
| <i >tablet_mac</i> | *tablet_mac* |
| <i >toys</i> | *toys* |
| <i >tv</i> | *tv* |
| <i >watch</i> | *watch* |

Loading [MathJax]/jax/output/HTML-CSS/jax.js