

WML - WML2.0 TAGS REFERENCE

http://www.tutorialspoint.com/wml/wml2_tags_reference.htm

Copyright © tutorialspoint.com

Here is a complete list of all the WML2 elements. Most of the elements are available in XHTML specification except few elements starting with *WML*: These elements are specific to WML.

All the elements have same meaning here what they have in XHTML specification.

Element	Attributes	Description
a	• id • class • title • style • xml:lang • href • charset • type • hreflang • rel • rev(• accesskey • tabindex	Specifies an anchor
abbr	• id • class • title • style • xml:lang	Specifies an abbreviation
acronym	• id • class • title • style • xml:lang	Specifies an acronym
address	• id • class • title • style • xml:lang	Specifies an address element

b	• id • class • title • style • xml:lang	Specifies bold text
base	• href	Specifies a base URL for all the links in a page
big	• id • class • title • style • xml:lang	Specifies big text
blockquote	• id • class • title • style • xml:lang • cite	Specifies a long quotation
body	• id • class • title • style • xml:lang • wml:newcontext • wml:onenterforward • wml:onenterbackward • wml:ontimer	Specifies the body element
br	• id • class • title • style	Inserts a single line break
caption	• id	Specifies a table caption

	• class • title • style • xml:lang	
cite	• id • class • title • style • xml:lang	Specifies a citation
code	• id • class • title • style • xml:lang	Specifies computer code text
dd	• id • class • title • style • xml:lang	Specifies a definition description
div	• id • class • title • style • xml:lang	Specifies a section in a document
dl	• id • class • title • style • xml:lang	Specifies a definition list
dt	• id • class • title • style	Specifies a definition term

	• xml:lang	
em	• id • class • title • style • xml:lang	Specifies emphasized text
fieldset	• id • class • title • style • xml:lang	Specifies a fieldset
form	• id • class • title • style • xml:lang • action • method • enctype	Specifies a form
h1...h6	• id • class • title • style • xml:lang	Specifies header 1 to header 6
head	• profile • xml:lang	Specifies information about the document
hr	• id • class • title • style • xml:lang	Specifies a horizontal rule
html		Starts of WML document

- version
- xml:lang
- xmlns:wml
- wml:onenterforward
- wml:onenterbackward
- wml:ontimer
- wml:use-xml-fragments

i

Specifies italic text

- id
- class
- title
- style
- xml:lang

img

Specifies an image

- id
- class
- title
- style
- xml:lang
- src
- alt
- longdesc
- height
- width
- wml:localsrc
- wml:type
- vspace
- hspace
- align

input

Specifies an input field

- id
- class
- title
- style
- xml:lang
- type
- name
- checked
- maxlength

- src
- tabindex
- accesskey
- wml:format
- wml:emptyok
- wml:name

kbd

Specifies keyboard text

- id
- class
- title
- style
- xml:lang

label

Specifies a label for a form control

- id
- class
- title
- style
- xml:lang
- for
- accesskey

li

Specifies a list item

- id
- class
- title
- style
- xml:lang

link

Specifies a resource reference

- id
- class
- title
- style
- xml:lang
- charset
- href
- hreflang
- type
- rel
- rev
- media

meta	• xml:lang • http-equiv • name • content • scheme • wml:forua	Specifies meta information
link	• id • class • title • style • xml:lang • declare • classid • codebase • data • type • codetype • archive • standby • height • width • name • tabindex	Specifies a resource reference
ol	• id • class • title • style • xml:lang	Specifies an ordered list
optgroup	• id • class • title • style • xml:lang • disabled • label	Specifies an option group

option	• id • class • title • style • xml:lang • selected • value • wml:onpick	Specifies an option in a drop-down list
p	• id • class • title • style • xml:lang • wml:mode • align	Specifies a paragraph
param	• id • name • value • valuetype • type	Specifies a parameter for an object
pre	• id • class • title • style • xml:lang • xml:space	Specifies preformatted text
q	• id • class • title • style • xml:lang • cite	Specifies a short quotation
samp	• id	Specifies sample computer code

- class
- title
- style
- xml:lang
- cite

select

Specifies a selectable list

- id
- class
- title
- style
- xml:lang
- name
- size
- multiple
- tabindex
- wml:iname
- wml:value
- wml:ivalue
- wml:name

small

Specifies small text

- id
- class
- title
- style
- xml:lang

span

Specifies a section in a document

- id
- class
- title
- style
- xml:lang

strong

Specifies strong text

- id
- class
- title
- style
- xml:lang

style

Specifies a style definition

- title

- xml:lang
- type
- media
- xml:space

table

Specifies a table

- id
- class
- title
- style
- xml:lang
- summary
- wml:columns
- wml:align

td

Specifies a table cell

- id
- class
- title
- style
- xml:lang
- abbr
- axis
- headers
- scope
- rowspan
- colspan
- align
- valign

textarea

Specifies a text area

- id
- class
- title
- style
- xml:lang
- name
- rows
- cols
- tabindex
- accesskey
- wml:format

	• wml:emptyok • wml:name	
th	• id • class • title • style • xml:lang • abbr • axis • headers • scope • rowspan • colspan • align • valign	Specifies a table header
title	• xml:lang	Specifies the document title
tr	• id • class • title • style • xml:lang • align • valign	Specifies a table row
u	• id • class • title • style • xml:lang	Specifies underlined text
ul	• id • class • title • style • xml:lang	Specifies an unordered list

var	• id • class • title • style • xml:lang	Specifies a variable
wml:access	• id • class • title • style • domain • path	Specifies access control information for the entire document
wml:anchor	• id • class • title • style • xml:lang • accesskey	Defines a source anchor for a hyperlink that may be activated by the user
wml:card	• id • class • title • style • xml:lang • anewcontext • onenterforward • onenterbackward • ontimer	Specifies a fragment of the document body
wml:do	• id • class • title • style • xml:lang • role	Provides a general mechanism for the user to act upon the current body/card. A task is associated with the wml:do element and that task is executed when the user activates the element.
wml:getvar	• id	Used to substitute the value of a variable into the text of a document.

- class
- title
- style
- name
- conversion

wml:go

The href attribute specifies a destination URI.

- id
- class
- title
- style
- href
- sendreferer
- method
- enctype
- acceptcharset
- cache-control
- type

wml:noop

Specifies that nothing should be done when an event occurs

- id
- class
- title
- style

wml:onevent

Binds a task to a particular event for the immediately enclosing element

- id
- class
- title
- style
- type

wml:postfield

Used to indicate an instance of a variable or program argument. The name attribute specifies the field name. The value attribute specifies the field value.

- id
- class
- title
- style
- name
- value

wml:prev

Declares a prev task, indicating navigation to the previous URI on the history stack.

- id
- class
- title

	• style	
wml:refresh	• id • class • title • style	Declares a refresh task, indicating an update of the user agent context as specified by the wml:setvar elements.
wml:setvar	• id • class • title • style • name • value	Specifies the variable to set in the current browser context as a side effect of executing a task. The name attribute specifies the name of the variable. The value attribute specifies the expression to evaluate and assign the variable.
wml:timer	• id • class • title • style • name • value	Declares a timer for a card or body, which exposes a means of processing inactivity or idle time.
wml:widget	• id • class • title • style • xml:lang • type • require-key • minlength	The wml:do element can contain zero or more wml:widget elements. These wml:widget elements represent possible widgets that may be used to present the wml:do element.