

WML <ANCHOR> TAG

http://www.tutorialspoint.com/wml/wml_anchor_tag.htm

Copyright © tutorialspoint.com

The <anchor>...</anchor> tag pair is used to create an anchor link. It is used together with other WML elements called <go/>, <refresh> or <prev/>. These elements are called task elements and tell WAP browsers what to do when a user selects the anchor link

You can enclose Text or image along with a task tag inside <anchor>...</anchor> tag pair.

Attributes:

This element supports the following attributes:

Attribute	Value	Description
title	cdata	Defines a text identifying the link
xml:lang	language_code	Sets the language used in the element
class	class data	Sets a class name for the element.
id	element ID	A unique ID for the element.

Example:

Following is the example showing usage of this element.

```
<?xml version="1.0"?>
<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.2//EN"
"http://www.wapforum.org/DTD/wml12.dtd">

<wml>

<card title="Anchor Element">
<p>
    <anchor>
        <go href="nextpage.wml"/>
    </anchor>
</p>
<p>
    <anchor>
        <prev/>
    </anchor>
</p>
</card>

</wml>
```

This will produce the following result:

Anchor Element	
nextpage.wml Back	
Options	Back