

WML <CARD> TAG

http://www.tutorialspoint.com/wml/wml_card_tag.htm

Copyright © tutorialspoint.com

The <card> element encloses a WML card within a deck. In addition, text and graphics enclosed within <p> elements, it may also contain a number of event bindings

Attributes:

The <card> element supports the following attributes:

Attribute	Value	Description
title	cdata	Gives a title to this card. This title is displayed in some way by the browser when the card is visible.
newcontext	<ul style="list-style-type: none">• true• false	Specifies that when this card is entered, the browser context should be cleared.
ordered	<ul style="list-style-type: none">• true• false	Provides a hint to the browser about how the card is organized. Set it to true if the card consists of a number of separate fields that should be dealt with in the order they appear in the card. Set it to false if the card contains optional fields or may be filled in out of order.
onenterforward	URL	Occurs when the user navigates into a card using a "go" task
onenterbackward	URL	Occurs when the user navigates into a card using a "prev" task
ontimer	URL	Occurs when a "timer" expires
xml:lang	language_code	Sets the language used in the element.
class	cdata	Sets a class name for the element.
id	element_ID	A unique ID for the element.

Example:

Following is the example showing usage of this element:

```
<?xml version="1.0"?>
<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.2//EN"
"http://www.wapforum.org/DTD/wml12.dtd">
<wml>

<card >
<p>
This is the first card in the deck
</p>
</card>

<card >
<p>
Ths is the second card in the deck
</p>
</card>
```

</wm1>