

WML <TABLE> TAG

http://www.tutorialspoint.com/wml/wml_table_tag.htm

Copyright © tutorialspoint.com

The <table> element along with <tr> and <td> is used to create a table in WML. WML does not allow the nesting of tables

A <table> element should be put with-in <p>...</p> elements.

Attributes:

The <table /> element supports the following attributes:

Attribute	Value	Description
columns	number	Sets the number of columns in the table
align	• L • C • R	To specify the horizontal text alignment of the columns, you need to assign three letters to the align attribute. Each letter represents the horizontal text alignment of a column. The letter can be L, C, or R. For example, if you want the following settings to be applied to your table: • First table column -- Left-aligned • Second table column -- Center-aligned • Third table column -- Right-aligned Then you should set the value of the <i>align</i> attribute to LCR.
xml:lang	language_code	Sets the language used in the element
class	class data	Sets a class name for the element.
id	element ID	A unique ID for the element.

Example:

Following is the example showing usage of <table> element.

```
<?xml version="1.0"?>
<!DOCTYPE wml PUBLIC "-//WAPFORUM//DTD WML 1.2//EN"
"http://www.wapforum.org/DTD/wml12.dtd">

<wml>

<card title="WML Tables">
<p>
<table columns="3" align="LCR">
  <tr>
    <td>Col 1</td>
    <td>Col 2</td>
    <td>Col 3</td>
  </tr>

  <tr>
    <td>A</td>
    <td>B</td>
    <td>C</td>
  </tr>

</tr>
```

```
<td>D</td>
<td>E</td>

<td>F</td>
</tr>
</table>
</p>
</card>

</wml>
```

This will produce the following result:

WML Tables		
Col 1	Col 2	Col 3
A	B	C
D	E	F
Options		Back