

XHTML - ATTRIBUTES

http://www.tutorialspoint.com/xhtml/xhtml_attributes.htm

Copyright © tutorialspoint.com

There are a few XHTML/HTML attributes which are standard and associated to all the XHTML/HTML tags. These attributes are listed here with brief description –

Core Attributes

Not valid in base, head, html, meta, param, script, style, and title elements.

Attribute	Value	Description
class	class_rule or style_rule	The class of the element.
Id	id_name	A unique id for the element.
style	style_definition	An inline style definition.
Title	tooltip_text	A text to display in a mouse tip.

Language Attributes

The **lang** attribute indicates the language being used for the enclosed content. The language is identified using the ISO standard language abbreviations, such as **fr** for French, **en** for English, and so on. More codes and their formats are described at www.ietf.org.

Not valid in base, br, frame, frameset, hr, iframe, param, and script elements.

Attribute	Value	Description
dir	ltr rtl	Sets the text direction.
lang	language_code	Sets the language code.

Microsoft Proprietary Attributes

Microsoft introduced a number of new proprietary attributes with the Internet Explorer 4 and higher versions.

Attribute	Value	Description
accesskey	character	Sets a keyboard shortcut to access an element.
language	string	This attribute specifies the scripting language to be used with an associated script bound to the element, typically through an event handler attribute. Possible values might include JavaScript, jScript, VBS, and VBScript.
tabindex	number	Sets the tab order of an element.
contenteditable	boolean	Allows users to edit content rendered in Internet Explorer 5.5 or greater. Possible values are true or false.
disabled	boolean	Elements with the disabled attribute set may appear faded and will not respond to user input. Possible values are true or false.
hidefocus	on or off	This proprietary attribute, introduced with Internet Explorer 5.5, hides focus on an element's content. Focus must be applied to the

element using the tabindex attribute.

unselectable

on or off

Used to prevent content displayed in Internet Explorer 5.5 from being selected.